

SOT23 PNP SILICON PLANAR MEDIUM POWER TRANSISTOR

FMMT591A


ISSUE 3 - OCTOBER 1995

FEATURES

Low equivalent on resistance $R_{CE(sat)} = 350m\Omega$ at 1A

PART MARKING DETAIL - 91A

COMPLEMENTARY TYPE - FMMT491A



ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Base Voltage	V_{CBO}	-40	V
Collector-Emitter Voltage	V_{CEO}	-40	V
Emitter-Base Voltage	V_{EBO}	-5	V
Peak Pulse Current	I_{CM}	-2	A
Continuous Collector Current	I_C	-1	A
Base Current	I_B	-200	mA
Power Dissipation at $T_{amb}=25^\circ\text{C}$	P_{tot}	500	mW
Operating and Storage Temperature Range	$T_j; T_{stg}$	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$).

PARAMETER	SYMBOL	MIN.	MAX.	UNIT	CONDITIONS.
Collector-Base Breakdown Voltage	$V_{(BR)CBO}$	-40		V	$I_C = -100\mu\text{A}$
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	-40		V	$I_C = -10\text{mA}^*$
Emitter-Base Breakdown Voltage	$V_{(BR)EBO}$	-5		V	$I_E = -100\mu\text{A}$
Collector Cut-Off Current	I_{CBO}		-100	nA	$V_{CB} = -30\text{V}$
Emitter Cut-Off Current	I_{EBO}		-100	nA	$V_{EB} = -4\text{V}$
Collector-Emitter Cut-Off Current	I_{CES}		-100	nA	$V_{CES} = -30\text{V}$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$		-0.2 -0.35 -0.5	V	$I_C = -100\text{mA}, I_B = -1\text{mA}^*$ $I_C = -500\text{mA}, I_B = -20\text{mA}^*$ $I_C = -1\text{A}, I_B = -100\text{mA}^*$
Base-Emitter Saturation Voltage	$V_{BE(sat)}$		-1.1	V	$I_C = -1\text{A}, I_B = -50\text{mA}^*$
Base-Emitter Turn-on Voltage	$V_{BE(on)}$		-1.0	V	$I_C = -1\text{A}, V_{CE} = -5\text{V}^*$
Static Forward Current Transfer Ratio	h_{FE}	300 300 250 160 30	800		$I_C = -1\text{mA}, I_C = -100\text{mA}^*, I_C = -500\text{mA}^*, V_{CE} = -5\text{V}$ $I_C = -1\text{A}^*, I_C = -2\text{A}^*,$
Transition Frequency	f_T	150		MHz	$I_C = -50\text{mA}, V_{CE} = -10\text{V}$ $f = 100\text{MHz}$
Output Capacitance	C_{obo}		10	pF	$V_{CB} = -10\text{V}, f = 1\text{MHz}$

*Measured under pulsed conditions. Pulse width=300 μs . Duty cycle $\leq 2\%$

Spice parameter data is available upon request for this device

FMMT591A

TYPICAL CHARACTERISTICS

