




2SD1433

NPN TRIPLE DIFFUSED PLANAR SILICON TRANSISTOR

COLOR TV HORIZONTAL OUTPUT APPLICATIONS (No Damper Diode)

- High Collector-Base Voltage($V_{CBO}=1500V$)



- High Speed Switching

ABSOLUTE MAXIMUM RATINGS ($T_A=25^{\circ}C$)

Characteristic	Symbol	Rating	Unit
Collector-Base Voltage	V_{CBO}	1500	V
Collector-Emitter Voltage	V_{CEO}	600	V
Emitter-Base voltage	V_{EBO}	6	V
Collector Current (DC)	I_C	5	A
Collector Dissipation ($T_c=25^{\circ}C$)	P_C	80	W
Junction Temperature	T_j	150	$^{\circ}C$
Storage Temperature	T_{stg}	-50~150	$^{\circ}C$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}C$)

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Collector- Emitter Cutoff Current($V_{BE}=0$)	I_{CES}	$V_{CE}=800V, R_{BE}=0$			1.0	mA
Collector Cutoff Current	I_{CBO}	$V_{CB}=600V, I_E=0$			10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=4V, I_C=0$			1.0	mA
DC Current Gain	hFE	$V_{CE}=5V,$	8			
Collector- Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=1A,$ $I_C=5A,$ $I_B=1A$			5.0	V

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.